

■NOTE■

- All materials applied are suitable in specified ambient temperature.
- KCE Inc reserves the right to alter or amend the above information without notice.
- According to detail drawing, the drawing can be changed.

S P E C I F I C A T I O N			
HOISTING LOAD		1000	KG
TESTING LOAD		1250	KG
LIFT		18	M
RATING		30	MIN
HOISTING (40% ED)	SPEED	HIGH	10 M/MIN
		CREEP	1 M/MIN
	MOTOR	HIGH	2.4 KW x 4 P
		CREEP	0.4 KW x 4 P
	BRAKE	DC MAG' DISC BRAKE	
TRAVERSING (40% ED)	SPEED	HIGH	20 M/MIN
		LOW	13 M/MIN
	MOTOR (1UNIT)	HIGH	0.4 KW x 4 P
		LOW	0.2 KW x 6 P
	BRAKE	DC MAG' DISC BRAKE	
WIRE ROPE		(6x37)+FC Ø8 x 2 FALLS	
POWER SOURCE		AC 3phase 380V, 415V 50Hz 440V, 480V	
TRAVERSING RAIL		I-BEAM / H-BEAM	
AMBIENT TEMPERATURE		0°C...+45°C	
WEIGHT		287 KG	
REMARK			

BASE OF DUTY

HOISTING : FEM 2m, ISO M5
CROSS TRAVEL : FEM 2m, ISO M5

THIS DRAWING IS THE PROPERTY OF KCE Inc COMPANY LIMITED AND MUST NOT BE PASSED ON TO ANY PERSON OR BODY NOT AUTHORISED BY US TO RECEIVE IT NOR BE COPIED OR OTHERWISE MADE USE EITHER IN PART BY SUCH PERSON OR BODY WITHOUT OUR PRIOR PERMISSION IN WRITING.

						
						
	2024.02.26	ISSUE FOR APPROVAL	Y.K.SEO	J.G.SHIN	M.G.SHIN	R.B.PA
No.	Date	Description	Drawn	Checked	Reviewed	Approved